



**Рабочая температура:** от -30°C до +60°C

**Temperature range:** -30°C - +60°C

**Цвет:** серый

**Color:** grey

**Свойства:** очень эластичный шланг из ПВХ, армированный усиливающей спиралью из устойчивого к ударам и давлению ПВХ. Внутренняя поверхность гладкая, внешняя слегка ребристая. Это исполнение является чрезвычайно износостойким и гибким. Устойчив к воздействию давления и абразивному износу, к ультрафиолетовому облучению и атмосферным явлениям, к воздействию большого числа химических веществ.

**Features:** Plasticized PVC hose with super elastic material, incorporated reinforcement of anti-shock rigid PVC spiral. Inside surface smooth, light corrugation outside. Very strong and flexible, is resistant to crushing, abrasion, to atmospheric agents and to most chemicals.

**Области применения:** для систем орошения, очистки канализации и сточных ям.

**Applications:** Irrigation, sink, spurging. Due to the high flexibility, is highly recommended for use on tank trucks.

Внутренний диаметр [мм]	Вес [г/м]	Толщина стенки [мм]	Радиус изгиба [мм]	Рабочее давление [бар]	Макс. давление [бар]	Вакуум [м/Н <sub>2</sub> O]	Упаковка [м]	Объем упаковки [м <sup>3</sup> ]
20	310	3,6	80	7	21	10	30	0,046
25	410	3,8	100	7	21	10	30	0,059
30	550	4,0	120	7	21	10	30	0,074
32	600	4,0	130	7	21	10	30	0,083
35	630	4,2	140	6	18	10	30	0,107
38	700	4,4	155	6	18	10	30	0,127
40	730	4,5	160	6	18	10	30	0,149
45	850	4,5	180	6	18	10	30	0,176
50	1000	4,8	200	5	15	10	30	0,207
60	1250	5,0	240	4,5	13,5	9	30	0,288
63	1390	5,2	260	4,5	13,5	9	30	0,288
70	1600	5,5	280	4,5	13,5	9	30	0,388
76	1700	5,5	310	4	12	9	30	0,417
80	1850	6,3	320	3,5	10,5	9	30	0,454
90	2150	6,3	360	3,5	10,5	9	30	0,689
100	2700	6,7	410	3	9	8,5	30	0,820
110	3000	7,0	450	3	9	8,5	30	0,995
120	3350	7,5	480	2,5	7,5	8	30	1,156
127	3600	7,5	510	2,5	7,5	8	30	1,243
150	5000	9,0	610	2	6	8	20	1,360
160	5600	9,5	650	2	6	7	20	1,500
180	6800	9,5	850	2	6	7	10	1,100
200	8000	9,5	1000	2	6	7	10	1,400



ИП «ДЛпласт»

IP DLplast

Республика Беларусь, г. Минск, 220075, ул. Инженерная, 3

Republic Belarus, Minsk, 220075, Ingenernaya, 3

(+375 17) 3449752, 3449499, 2996105, 2996092

[www.dlplast.com](http://www.dlplast.com)

e-mail: [dlplast@mail.ru](mailto:dlplast@mail.ru)